

Registration no:

--	--	--	--	--	--	--	--	--	--

Total Number of Pages: 02

B.Tech
PEME5401

7th Semester Regular / Back Examination 2017-18
Mechanical Vibration
BRANCH: Mech
Time: 3 Hours
Max Marks: 70
Q.CODE: B411

Answer Question No.1 which is compulsory and any five from the rest.
The figures in the right hand margin indicate marks.

- Q1 Answer the following questions: (2 x 10)**
- a) Discuss the effect of inertia of a shaft on the free torsional vibration.
 - b) Explain why the mass, damping and stiffness matrices are symmetrical?
 - c) What is the equivalent stiffness of spring connected in parallel having stiffness k_1 and k_2 ?
 - d) What is the cause and effect of vibration?
 - e) List four differences between the free vibrations of an under damped system and a system with Coulomb damping.
 - f) Explain the concept of hysteresis? What is the area under a hysteresis cycle?
 - g) What is a node? Describe with neat sketch.
 - h) Define free vibration, forced vibration and damped vibrations.
 - i) Explain how the natural frequency of torsional vibration for a two rotor system is obtained?
 - j) A mass of 12 kg is attached to two springs each of stiffness 4000 N/m and mounted in parallel. What is the natural frequency of the system?
- Q2 a) Explain an expression for amplitude of forced vibration. (5)**
- b) What is static and dynamic coupling? How can you eliminate coupling of the equation of motion? (5)**
- Q3 a) A 65 kg industrial sewing machine operates at 125 Hz and has a rotating unbalance of 0.15 kg·m. The machine is mounted on a foundation with a stiffness of 2×10^6 N/m and a damping ratio of 0.12. Determine the machine's steady amplitude. (5)**

- b) Explain the whirling of shaft (5)
- Q4** a) A 50-kg machine tool is mounted on an elastic foundation that is modeled as a spring and viscous damper in parallel. In order to determine the properties of the foundation, a force with a magnitude of 8000 N is applied to the machine tool at a variety of speeds. It is observed that the maximum steady-state amplitude is 2.5 mm, which occurs at 35 Hz. Determine the equivalent stiffness and equivalent damping coefficient of the foundation. (5)
- b) Why can't the concept of logarithmic decrement be used to measure viscous damping ratios greater than or equal to one? Explain. (5)
- Q5** a) Derive the expression for free torsional vibration fixed at one end and carrying a load on the free end. (5)
- b) A 40 kg pump is to be placed at the midspan of a 2.5-m long steel ($E = 200 \times 10^9$ N/m²) beam. The pump is to operate at 3000 rpm. For what values of the cross-sectional moment of inertia will the oscillations of the pump be within 3 Hz of resonance? (5)
- Q6** a) Discuss the effect of inertia of the shaft in longitudinal and transverse vibration. (5)
- b) Describe the method of finding the natural frequency of torsional vibration for a three rotor system. (5)
- Q7** A flow-monitoring device of mass 10 kg is to be installed to monitor the flow of a gas in a manufacturing process. Because of the operation of pumps and compressors, the floor of the plant vibrates with amplitude of 4 mm at a frequency of 2500 rpm. Effective operation of the flow-monitoring device requires that its acceleration amplitude be limited to 5g. What is the equivalent stiffness of an isolator with a damping ratio of 0.05 to limit the transmitted acceleration to an acceptable level? What is the maximum displacement of the flow-monitoring device and what is the maximum deformation of the isolator? (10)
- Q8** Write short answer on any TWO: (5 x 2)
- a) Vibration isolation
 - b) Accelerometer
 - c) Orthogonality of mode shapes
 - d) Transverse vibration of Euler-beams